

Hot Rolled Coils and Plates

Available in spec and grades:

JIS G3101 SS400, SS490

EN 10025-2:2004 S235JR, S275JR/J0/J2, S355JR/J0/J2/K2

ASTM A36, A572 Gr 50

Dimensions and tolerances as per

JIS G3193:2008

EN 10029:2010

ASTM A6/A6M

Thickness t (mm)	G (kg/m)	Width x Length b x l (mm)						
		914 x 1828	1000 x 2000	1219 x 2438	1500 x 6000	2000 x 12000	2500 x 12000	3050 x 12000
2	15.7	26.23	31.4	46.66				
3	23.55	39.35	47.1	69.99	211.95			
4	31.4	52.46	62.8	93.32	282.6	753.6		
5	39.25	65.58	78.5	116.65	353.25	942	1177.5	
6	47.1	78.69	94.2	139.98	423.9	1130.4	1413	1723.86
8	62.8	104.93	125.6	186.64	565.2	1507.2	1884	2298.48
10	78.5	131.16	157	233.3	706.5	1884	2355	2873.1
12	94.2	157.39	188.4	279.96	847.8	2260.8	2826	3447.72
14	109.9	183.62	219.8	326.61	989.1	2637.6	3297	4022.34
15	117.75	196.74	235.5	349.94	1059.75	2826	3532.5	4309.65
16	125.6	209.85	251.2	373.27	1130.4	3014.4	3768	4596.96
18	141.3	236.08	282.6	419.93	1271.7	3391.2	4239	5171.58
20	157	262.31	314	466.59	1413	3768	4710	5746.2
22	172.7	288.55	345.4	513.25	1554.3	4144.8	5181	6320.82
25	196.25	327.89	392.5	583.24	1766.25	4710	5887.5	7182.75
30	235.5		471	699.89	2119.5	5652	7065	8619.3
32	251.2			746.55	2260.8	6028.8	7536	9193.92
35	274.75			816.54	2472.75	6594	8242.5	10055.85
38	298.3			886.52	2684.7	7159.2	8949	10917.78
40	314			933.18	2826	7536	9420	11492.4
45	353.25			1049.83	3179.25	8478	10597.5	12928.95
50	392.5			1166.48	3532.5	9420	11775	14365.5
55	431.75			1283.13		10362		
60	471			1399.78		11304		
70	549.5			1633.07		13188		
75	588.75			1749.72		14130		
80	628			1866.37		15072		
90	706.5			2099.66		16956		
100	785			2332.96		18840		

